

# Technical Datasheet



Nuva Selected DRYBACK acc. ISO 19322:2018-03

Use class 34/42 acc. DIN EN ISO 10874:2021-04

Version: 10/2024


**Core board:** Classen Ceramin-Board  
**Dimensions:** 1290 x 210 x 2.5 mm  
**Content / Weight per box:** 16 pieces = 4.334 m<sup>2</sup> / approx. 16 kg  
**Content / Weight per pallet:** 48 PU = 203.90 m<sup>2</sup> / approx. 793 kg  
**Surface structure:** Matt Timberland 2.0

# NUVA

Characteristic	Method	Requirement
<b>General Requirements</b>		
Length / Width	ISO 24342	Length: ≤ 0.13% max. 0.5 mm Width: ≤ 0.10% max. 0.5 mm
Overall thickness	ISO 24346	+ 0.13 mm - 0.10 mm
Squareness	ISO 24342	max. ≤ 0.25 mm
Straightness	ISO 24332	max. ≤ 0.35 mm
Thickness of the wear layer	ISO 24340	Ø ≤ + 13% Ø ≥ - 10%
Total mass per unit area	ISO 23997	Ø ≤ + 13% Ø ≥ - 10%
Dimensional stability after exposure to heat (Method B / 6 h at 50°C)	ISO 23999	≤ 0.25 %
Curling after exposure to heat (Method B / 6 h at 50°C)	ISO 23999	≤ 2 mm
Light fastness 	EN ISO 105-B02	Blue wool scale ≥ 6
<b>Classification requirements</b>		
Total thickness	ISO 24346	≥ 2 mm
Residual indentation 	EN ISO 24343-1	≤ 0.1 mm
Scratch resistance	ISO 19322 (Annex A)	≥ 3 N
Simulated movement of a furniture leg 	ISO 16581	No visual damage type 2 (100 kg)
Castor chair resistance 	ISO 4918	No visual damage type W (25,000 cycles)
<b>Essential characteristics</b>		
Fire behaviour* 	EN 13501-1	B <sub>fl</sub> - s1
Slip resistance* 	EN 13893 DIN EN 16165 (Annex B)	DS R10
Formaldehyde content* 	EN 16516	Not added
Thermal resistance 	EN 12667	R ≤ 0.013 m <sup>2</sup> K/W
PCP content	CEN/TR 14823	PCP free
<b>Additional characteristics</b>		
Abrasion resistance 	ISO 24338 (Method B)	≥ 7,000 Cycles
Impact resistance 	EN 13329:2006	≥ 1,800 mm
Micro scratch resistance	EN 16094 (Method A)	≤ MSR A 2
Stain resistance 	EN 438-2	5 (Group 1 and 2), 4 (Group 3)
Swelling 	ISO 24336	No swelling
<b>Environmental characteristics</b>		
Composition	No halogenes or phthalates added	
VOC Emissions	  <a href="http://www.blauer-engel.de/v2120">www.blauer-engel.de/v2120</a> - low VOC content - low phthalate content - no adverse impact on health in the living environment	
Share post consumer recycle	 	

Disposal: Private: with normal household waste / bulky waste possible | Commercial: European Waste Catalog: Waste code 17 02 03

We guarantee consistency of our decor colours under artificial light of type D50 (CIE D50, ANSI PH 2.30, ISO 3664) and D65 (CIE D65).

\* basic attributes concerning health, safety and energy saving acc. to  EN 14041

Our technical data sheets are constantly updated and adapted to the state of the art.

CLASSEN Holz Kontor GmbH, Werner-von-Siemens-Str. 18-20, DE-56759 Kaisersesch

This edition replaces all previous versions and is valid at the time of writing.

This document is valid without signature.