

# Technisches Datenblatt

Nuva Rock 40/80 Click

Class 34 according to DIN EN 16511:2025-07

# NUVA

# CLASSEN

Version: 02/2026

**Core board:** Classen Ceramin-Board  
**Dimensions:** 776 x 387 x 4.5+1 mm  
**Quantity / Weight per box (PU):** 8 pieces = 2.402 m<sup>2</sup> / approx. 18 kg  
**Quantity / Weight per pallet:** 45 PU = 108.09 m<sup>2</sup> / approx. 820 kg  
**Surface structure:** Minipearl 2.0

**Profile:**

## MEGALOC

AQUAPROTECT

Characteristics	Test Method	Requirements
<b>General Requirements</b>		
Geometrical characteristics	EN 17539	Length: ± 0.5 mm Width: ± 0.1 mm
Total thickness	EN 17539	± 0.8 mm
Squareness	EN 17539	max. ≤ 0.20 mm
Flatness of the elements	EN 17539	Length: concave ≤ 0.50 %, convex ≤ 1.00 % Width: concave ≤ 0.15 %, convex ≤ 0.20 %
Straightness	EN 17539	max. ≤ 0.30 mm/m
Openings	EN 17539	Ø ≤ 0.15 mm max. ≤ 0.20 mm
Height difference	EN 17539	Ø ≤ 0.10 mm max. ≤ 0.15 mm
Light fastness	EN ISO 105-B02	Blue Wool Scale ≥ 6
Determination of dimensional stability and curling after exposure to heat	EN ISO 23999	Δl ≤ 0.15 % ≤ 2 mm
<b>Classification Requirements</b>		
Wear resistance	ISO 24338 (Method B)	≥ 7,000 Cycles
Impact resistance	EN 13329:2006	≥ 1,800 mm
Micro-scratch resistance	EN 16094	≤ MSR - A2 I ≤ 1 unit change I at 60°
Movement of a furniture leg	EN ISO 16581	No visible damage with type 0
Castor chair resistance	ISO 4918	No visible damage with type W (25,000 Cycles)
Residual indentation	EN ISO 24343-1	max. ≤ 0.15 mm
Resistance to staining	EN 438-2	5 (group 1 and 2), 4 (group 3)
Thickness swelling	ISO 24336	No swelling
Locking strength	ISO 24334	f <sub>0,2</sub> ≥ 1.0 kN/m f <sub>s0,2</sub> ≥ 1.5 kN/m
<b>Essential Characteristics</b>		
Reaction to fire*	EN 13501-1	C <sub>f</sub> - s1
Slip resistance*	EN 13893	DS
Electrical behaviour	EN 1815	Not antistatic
Formaldehyde*	EN 16516	Not added
Thermal resistance*	EN 12667	R ≤ 0.037 (m <sup>2</sup> K)/W
Reduction of transmitted impact noise with integrated underlay	EN ISO 10140-3	16 dB
PCP-Content	CEN/TR 14823	PCP free
<b>Additional Characteristics</b>		
Composition		No halogenes or phthalates added
VOC Emissions	  <a href="http://www.blauer-engel.de/uz120">www.blauer-engel.de/uz120</a> • low emissions • low pollutant content • no adverse impact on health in the living environment	 
Recycled content (Post Consumer)		

**Disposal: Private: with normal household waste / bulky waste possible | Commercial: European Waste Catalog: Waste code 17 02 03**

We guarantee consistency of our decor colours under artificial light of type D50 (CIE D50, ANSI PH 2.30, ISO 3664) and D65 (CIE D65).

\* basic attributes concerning health, safety and energy saving acc. to **CE** EN14041

Our technical data sheets are constantly updated and adapted to the state of the art.

CLASSEN Holz Kontor GmbH, Werner-von-Siemens-Str. 18-20, DE-56759 Kaisersesch

This edition replaces all previous versions and is valid at the time of writing.

This document is valid without signature.